# Multipurpose Portable Transformer Testing Kit

Prof. Rohan Ingle<sup>1</sup>, Priyanka Shende<sup>2</sup>, Monali Bhoyar<sup>3</sup>, Rupali Ukey<sup>4</sup>

<sup>1</sup>(Electrical, Jhulelal Institute Of Technology, India) <sup>2</sup>(Electrical, Jhulelal Institute Of Technology, India) <sup>3</sup>(Electrical, Jhulelal Institute Of Technology, India) <sup>4</sup>(Electrical, Jhulelal Institute Of Technology, India)

**Abstract:** A manufacture's own criteria have to be fulfilled in addition to requirements specified by customers and applicable standards. Manufacturers test thousands of distribution as well as power transformer at worldwide location each week. In this paper, I wish to give an overview about different test conducted in distribution as well as power transformer of rating up to 11KVA TO 25 MVA .Equipment use in testing single phase dimmer stat, multimeter, digital voltmeter, digital insulation resistance, tong tester, MCB, fuse, banana connector, switches, testing wire connecting wire.Testing of any electrical equipment indicate the extent to which the equipment is able to comply with customer's requirements .In this paper testing of distribution as well as power transformer considered.

*Keywords: Testing of banana connector, digital voltmeter, fuse, insulation resistance, MCB, single phase dimmer stat.* 

# I. Introduction

The five basic tests were Insulation Resistance, Turns Ratio, Magnetizing Balance, Magnetizing Current, Short Circuit test. For performing this above test they carried separate testing equipment for each test. The topic for project is "Multipurpose Transformer Testing Kit". The kit is designed for the purpose of testing of transformer at different site where transformer is installed, to verify the operation of the transformer .These all five tests require large number of equipment's to be carried separately when needed. This leads to increase in cost of transportation, more men power to carry them and chances of damaging the instruments when carried in bulk are high. Hence, finding solution to the problem, we designed a kit which can be carried by a single person having all the basic tests in one kit i.e. Insulation resistance test, turns ratio test, short circuit test, magnetizing current and magnetizing balance test. This kit is designed to test transformers of any rating. Thus, giving many advantages over the previous method. Now, this kit of cost of transportation and only one person will be sufficient to carry the kit as it is compact and brief case mounted making this kit an excellent device for a power transformer company to own. At site, to verify the operation of transformer the five basic tests have been performed on it.

# II. Methods

## **Procedure:**

1. First disconnect all the line and neutral terminals of the transformer.

2. Megger leads to be connected to LV and HV bushing studs to measure insulation resistance IR value in between the LV and HV windings.

3. Megger leads to be connected to HV bushing studs and transformer tank earth point to measure insulation resistance IR value in between the HV windings and earth.

4. Megger leads to be connected to LV bushing studs and transformer tank earth point to measure insulation resistance IR value in between the LV windings and earth. IR should be high i.e. Up to 1000mohm.it is 1 minute test & IR values to be recorded at intervals of 15 seconds, 1 minute.Turns ratio of a transformer is the ratio of number of turns in high voltage winding to that in low voltage winding.

2. Voltage ratio test: Turns ratio of a transformer is the ratio of number of turns in high voltage winding to that in low voltage winding.

International Conference on Innovations in Engineering, Technology, Science & Management – 26 | Page 2019 (ICI-ETSM-2019)



Procedure:

1) We just apply single phase supply to LV winding, with keeping LV winding open.

2) Then we measure the induced voltages at HV and LV terminals of transformer to find out actual voltage ratio of transformer.

- 3) We repeat the test for all tap position separately.
- 4) Take ratio of voltage at HV to LV and compare it with name plate ratio.
- 1. First keep the tap changer of transformer in normal position.
- 2. Now disconnect the transformer neutral from ground.
- 3. Then apply single phase 230 v ac supply across one of the HV winding terminals and neutral terminal.
- 4. Measure the voltage in two other HV terminals in respect of neutral terminal.
- 5. Repeat the test for each of the three phases.

The voltage induced in different phases of transformer in respect to neutral terminals given in the table below:

Applied voltage	RN	YN	BN
Voltage applied across R phase	100%	60 to 80%	40 to 20%
Voltage applied across Y phase	50%	100%	50%
Voltage applied across B hase	40 to 20%	60 to 80%	100%

# 4. Magnetizing current test:

Magnetizing current test of transformer is performed to locate defects in the magnetic core structure, shifting of windings, failure in turn to turn insulation or problem in tap changers. These conditions change the effective reluctance of the magnetic circuit, thus affecting the current required to establish flux in the core.



Procedure:

- 1. First of all keep the tap changer in the lowest position and open all HV and LV terminals.
- 2. Then apply single phase 230 v supply on transformers.
- 3. Measure the supply voltage and current in each phase.
- 4. Now repeat the magnetizing current test of transformer test with keeping tapchanger in normal position.
- 5. And repeat the test with keeping the tap at highest position.

International Conference on Innovations in Engineering, Technology, Science & Management – 27 | Page 2019 (ICI-ETSM-2019)

# 5. Short circuit test

In this test primary applied voltage, the current and power input is measured keeping the secondary terminals short circuited. The supply voltage required to circulate rated current through the transformer is usually very small and is of the order of a few percentage of the nominal voltage.

## Procedure:

1) Connect testing board HV wire to HV side of transformer.

2) Short LV winding of transformer.

3) Connect single phase supply to testing board.

4) Set the transformer on its maximum / normal / minimum position.

5) Switch on the single phase supply.

6) Check incoming supply with help of multimeter it should be 230 V.

7) Switch on M.C.B.

8) Measure HV voltage HV current & LV current.

9) After measuring all parameter switch off M.C.B.

Then by using formula find out the impedance of transformer

V <u>applied</u> x I <u>rated</u> x 100 % z = V rated I measured

% z = V rated I me Where

Wannied is voltage annlied to tran


V applied is voltage applied to transformer to HV side

V rated is rated voltage of transformer on HV side

I rated is rated current of transformer on LV side

I measured is measured current of transformer on LV side.

# **III. Circuit Diagram**



Description of circuit diagram :

□ □ Single phase 230 Volt AC supply is given to the dimmer stat of rating single phase 230 Volt 20 Amp.

- $\Box$   $\Box$  Output of the dimmer stat is display on the voltmeter.
- □ □ By using contactor, two wire systems is converted in to four wire system i.e. R, Y, B, neutal.
- $\Box$   $\Box$  These four wires are connected to the MCB of 32 Amp.
- $\Box$   $\Box$  Four wires from MCB are connected to the fuse then fuse to switches.
- $\Box$   $\Box$  From switches it is connected to the HV port of transformer.

International Conference on Innovations in Engineering, Technology, Science & Management – 28 | Page 2019 (ICI-ETSM-2019)

# **ACTUAL IMAGES:**

Hardware Components:

- 1. Single phase dimmer stat (1 phase 230V, 20 A)
- 2. Digital Voltmeter (650V)
- 3. Multimeter (10Amp, 600V)
- 4. Digital insulation tester (2000Mohm, 1KV)
- 5. Tong tester (1000)
- 6. MCB (miniature circuit breaker) (32Amp)
- 7. Fuse (5Amp, 230V AC)
- 8. Banana Connector.
- 9. Testing wire.
- 10. Connecting wire.

## **IV. Literature Survey**

1) 90 SM 317-8 JANUARY 1991 "REAOSANT POWER SUPPLY KIT SYSTEM FOR HIGH VOLTAGE TESTING" H. G. Gerlach Harns Kull AG, CH-4552 Derendingen Switzerland. In power engineering ,reasonce of narrow-band quality is not considered to be a steady-state operating condition .Frequency variation was therefore not applied in reasonant ac testing installation until the early eighties.

2) M. Wang and A. Vandemaar published that life of transformer can be as long as 60 years with appropriate maintenance. When transformer is new it has sufficient electrical and mechanical strength to withstand stresses. To prevent failure preventive maintenance is carried out by using traditional diagnostic techniques for detection of incipient fault in transformer.

3) Shivaji chakravorti has workshop at Maha Transco on condition monitoring of oil-paper composite insulation system of power transformer. He explained various diagnostic techniques used for power transformer. He explained various diagnosis techniques used for detection of incipient fault in Transformer .

4) January 2011 Geno Peter. P Department of electrical and electronics engineering Loyola Institute of Technology and science Loyola Nagar, Thovali, tamilnadu-629302, India

In this pepar three type of test are performed on transformer these are routine test ,type or Desing test, special or other test which require large number of equipment to verify each operation.

5) Dr .Jonathan Sturgess is a consultant for electromagnetic and electrical machines at AREVA T&D Technology Centre ,UK.

# V. Conclusion

1. After the completion of our project, the testing process will be improved.

2 .In previous methods as we had to carry different testing equipment's for various tests which causes trouble to carry huge luggage while going on site and there will be more chances of the equipment gets damaged. But in MPTT panel, the danger of equipment's getting damaged is reduced.

3. Use of digital equipment's such as voltmeter, ammeter, IR tester, and tong tester, multimeter provides minimization in errors and provide accurate.

4. In case of hand driven megger, for generation of 1kv we have to drive the megger manually until 1kv get generated which consumes time and more manual efforts is required. But in case of digital megger, 1KV can get easily genenerationfrom12V DC supply by pressing a button on megger which ultimately reduces time and no manual efforts are required.

# **VI. Future Scope**

We may use PLC SCADA or any other automation system to convert this manual operation of kit to automatic where the values for all the tests will be directly displayed on the screen.

## References

## **Journal Papers:**

[1] Anubhav Gupta, Abhinav Gupta, Testing of Transformers & Induction Machines, 5 April 2012.

- [3] Geno Peter. P, High Voltage Test Techniques, IEC 60060-1, January 2011.

International Conference on Innovations in Engineering, Technology, Science & Management – 29 | Page 2019 (ICI-ETSM-2019)

## **Books:**

- [4] Tata McGraw-Hill Education ,Transformer Testing ,(01 Jan 2003).
- [5] Wayne Smith, Transformer Inspection and Testing LSA; 1.1 edition (17August 2012).
- [6] James H Harlow, Electric Power Transformer Engineering, Third Edition (8 July 2014).
- [7] Electrical Technology by B. L. Theraja

# **Proceedings Papers:**

- [8] IEEE Std. 62-1995. IEEE Guide for Diagnostics Field Testing of Electric IEC 60076 -1.
- [9] IEEE Guide for Failure Investigation, Documentation, and Analysis for Power Transformers and Shunt Reactors, IEEEC57.125, May power transformers" –Part 1: General, 2000.
- [10] P. Gill, Electrical Power Equipment Maintenance and Testing, 2nd edition., CRC Press, Taylor & Francis Group. 2009.
- [11] American National Standards Institute, ANSI/NETA MTS-2011: Standard for Maintenance Testing Specifications for Electrical Power Equipment and Systems, May 2011